

SPECIFICATION & PROCEDURAL DATA SHEET

ORGANOIL -Woodsheen

DESCRIPTION:

Formulated from highly refined Natural Plant Oils and waxes. When applied and buffed over ORGANOIL'S Hard Burnishing Oil provides a soft, satin result. A low-build maintenance product designed to augment the appearance of existing oil-finished timbers. Woodsheen can also be used as a complete finish as described below.

USES:

INTERIOR ONLY – raising the patina/rejuvenating surfaces of ORGANOIL brand oil-finished Woodwork, Table, Bench & Bar-tops Furniture and Flooring.

Can be used as a complete finish on pale timbers when least yellowing/ darkening affect is required (refer to Special notes 3.)

Special Notes:

1. Woodsheen should ONLY be used over existing ORGANOIL brand products and should NOT be used over other brand finishes as it could be INCOMPATIBLE .If considering use over another brand product a test should be carried out in an inconspicuous area first
2. Woodsheen, as a low-build buffing oil will achieve SATIN results over a period of time where inter-spaced spray on and buffs are conducted.
3. If using as a finish on raw timber the application of many light coats is recommended see **NOTES** under application.

PREPARATION:

1. When using **WOODSHEEN** over existing **ORGANOIL** finish, **MAKE SURE** that a minimum of **1 – 2 weeks** has elapsed in order for that product to have thoroughly dried/cured.
2. Ensure surfaces are clean, dry and free of dirt, dust etc. prior to application.
3. Read and follow **Application and Maintenance** procedures carefully.

Coverage (approx)

Initial application/buff 22-30 sq mtr / litre

Maintenance/Rejuvenation 45-50 sq mtr / litre

APPLICATION: (use and allow to dry under good ventilation)

Firstly, ensure you have read, understood and followed above Uses, Notes and Preparation advice before commencing!

NOTES: If using as a finish on raw timber- (not for working or wet areas- Hard Burnishing Oil should be used in those areas first, then Woodsheen used later as a maintenance Oil)

- a) Sand timber (dry) through grits, 600 – 1500 (the finer sanded, the better the finish will be)
- b) Apply 2 coats 3-4 days apart – wipe off excess oil that has not been absorbed, within 1- 2 hours after each application
- c) Repeat steps in b) until the desired lustre is achieved (3-5 applications may be necessary depending on the lustre sought)
- d) 24 – 48 hours after the final application, buff well using a lint free cloth or lambs wool pad.

FLOOR MAINTENANCE/REJUVENATION:

- Note:**
- i. Aside from well placed entrance mats and felt under furniture contact points, you will further reduce wear by considering leaving shoes at entrances.
 - ii. For ease of maintenance, consideration should be given to purchasing a domestic polishing machine.

INITIAL PROCESS OVER BURNISHING FLOOR OIL

Ensure minimum of 12 weeks has elapsed since FLOORING OIL was applied .

Cleaning: Sweep, vacuum, or clean by mopping over with solution of warm water, methylated spirits and white vinegar (250ml of each per 10ltr bucket warm water) add mild detergent if very dirty.

Rejuvenation: With traffic/wear areas (clean first if necessary, then allow to dry) thoroughly buff or rub in small amount (mist spray on is best) of Organoil WOODSHEEN with cloth or lambs wool – walk on in 2 hours. It is normally recommended this maintenance be done 6 monthly but depending on condition of floor- high traffic areas may require a monthly treatment.

Repairing

Scratches: Using light quantities of oil as a lubricant lightly sand (with the grain) out scratches with wet and dry sand paper (240-400 grit) then cloth over.

Clean up: Hot soapy water or Pure Gum Turpentine

Storage:

- Store with lid tightly closed and in a cool, dry place.
- **KEEP OUT OF REACH OF CHILDREN**

WARNING!

- **AFTER USE SOAK CLOTHS IN WARM SOAPY WATER, RINSE AND HANG TO DRY**
(Oil is exothermic & oil soaked material may combust if left)
- **IF SWALLOWED SEEK MEDICAL ADVICE, DO NOT INDUCE VOMITING**
- **KEEP AWAY FROM IGNITION SOURCES**



SIZES AVAILABLE:
1, 2 & 4 Litres

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF THESE PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS ARE MADE WITHOUT GUARANTEE. NO REPRESENTATIVE OR AGENT OF OURS HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

ORGANOIL™ manufactured by **SALES FORCE NSW- 20 Queen Street, Revesby 2122 PH: 02 9773 9399**

Web site: www.organoil.com.au Email: tech@salesforcensw.com.au